

TVB-6104

TruVision HD-TVI analog bullet camera, 5MPX, 3.6 mm lens, WDR, 30 m IR,12 VDC, IP67

Product overview

The TruVision line includes a comprehensive family of HD-TVI infrared (IR) cameras for stand-alone or integrated installations. Designed for optimal image quality over existing coaxial cable, options are available at up to 8Mpx resolution.

Ideal for improving video quality of existing analog surveillance system installations ranging from convenience stores to retail mall parking lots, the TruVision HD-TVI line has the right cameras for your new or existing project and can help you stay within budget constraints without compromising security needs.

The cameras have true day/night capabilities, providing color images by day and black-and-white images under IR operation in low light applications. TruVision HD-TVI cameras are available with either fixed lens or varifocal lens.

Form factors include dome, traditional bullet and turret cameras . Bullet models offer a familiar form factor that features a pre-installed wall mount with cable management. All models are IP67 rated for outdoor installation and select dome models are available with an IK10 vandal-rated enclosure.

All TruVision HD-TVI cameras are designed to install quickly and easily, right out of the box, so you can be up and running in no time.



Details

- 5MPx HD-TVI resolution
- HD-TVI technology for transmitting high quality video over existing coax cable
- True day/night functionality and infrared illuminators with Smart IR function for capturing images in various lighting scenarios
- IR range of up to 30 m
- IP67 environmental rating
- True wide dynamic range
- 3.6 mm fixed lens
- 12 VDC
- Bracket included
- Provide OSD functionality via TruVision up the coax control

TVB-6104

TruVision HD-TVI analog bullet camera, 5MPX, 3.6 mm lens, WDR, 30 m IR,12 VDC, IP67

Technical specifications

General		
Technology	HD-TVI analog	
Video standard	NTSC, PAL	
Image settings	Mirror	
Video output	BNC Composite PAL / NTSC, HD-TVI	
Camera		
Max. resolution	5 MP	
Sensor scan	Progressive	
Sensor type	CMOS	
Effective pixels (H x V)	2560 x 1944	
Shutter time	1/25 s (PAL) or 1/30 s (NTSC) to 1/50,000	
Lighting performar	nce	
WDR type	True WDR	
WDR	130 dB	
Day/night	True Day/Night	
Motorized IR cut filter	Yes	
Color sensitivity	0.003 Lux @ (F1.2, AGC ON)	
B/W sensitivity	0 Lux with IR	
Infrared (IR)	Yes	
IR range	30 m	
Lens		
Lens type	Fixed	
Focal length	3.6 mm	
f-stop	f1.2	
Auto iris	Yes	
Electrical		
Operating voltage	12 VDC	
Power supply type	12 VDC	
Power consumption	5.8 W max.	
Physical		
Physical dimensions	58 x 61 x 158.6 mm	
Net weight	320 g	
Colour	Grey (Pantone 428c)	
Material	Aluminium	
Form Factor	Bullet	
Environmental		
Vandal proof	No	
Environment	Indoor, Outdoor	
Operating temperature	-40 to +60°C	
Relative humidity	<90%, noncondensing	
IP rating	IP67	
Regulatory		
Compliancy		

Compatible TruVision Recorders/Encoders

TVR12HD	(View max. 1080p, Record max. 1080p @ 12 fps)
TVR44HD	(Record/View max. 1080p)
TVR15HD	(Record/View max. 5Mpx @ 12fps)
TVR45HD	(Record/View max. 5Mpx @ 12fps)
TVR46HD	
TVE-110/410/810/1610	
TVE-120/420/820/1620	

Compatible products

Category	Reference	Description
Brackets &	TVB-2G-AD	TruVision 2 Gang Box Adapter Plate (for
Mounts		LWB mount and fixed lens bullet)
Brackets &	TVB-BB1	TruVision bullet camera back box (use
Mounts		with TVB fixed lens bullet)

